


# epGate PA

## Direct PROFIBUS PA Segment Integration into EtherNet/IP Control Systems

- Prepared for Integration in Standard Engineering and Plant Asset Management Tools
- Re-use of Existing Power Conditioners in Technology Upgrade Projects
- No PROFIBUS DP Intermediate Segment required
- Simple Integration Through Add-On Instructions



### Configuration, Parameterization and Plant Asset Management Using Standard Industry Tools

- Supports major EtherNet/IP engineering tools such as Studio 5000 and AMS Device Manager
- Included ComdDTM allowing use in FDT/DTM frame applications
- EDD-based device parameterization using Siemens Simatic PDM

### Key Component for Transition to State-of-the-Art Technology

- Simple replacement of installed PROFIBUS DP/PA segment couplers
- Re-use of existing PROFIBUS PA segments without requiring modification
- Support of common control systems e.g. Emerson DeltaV or Rockwell Control Logix
- Support of DLR for redundant communication in the ring with EtherNet/IP

### Direct Connectivity to PROFIBUS Segments

- Acting as EtherNet/IP device (adapter) and PROFIBUS PA Master
- Support of up to 4 PROFIBUS PA segments
- Support of up to 64 PROFIBUS devices

### Simple Integration Through Add-On Instructions

- Data access of PLC program to PROFIBUS devices without requiring detailed PROFIBUS knowledge
- Mapping between the two protocols generated by provided tools
- Use of Add-On Instructions (AOI) containing detailed PROFIBUS data type definitions
- Transparent communication overcoming protocol differences
- Optimized for usage with Allen Bradley controllers

# epGate PA

## Technical Data

<b>Hardware</b>	Processor	Altera Cyclone V SoC with dual-core ARM Cortex-A9
	Status LEDs (Gateway)	PWR (power supply), RUN (operation), ERR (error), CFG (configuration and update)
	Status LEDs (Fieldbus)	SF (system fault), BF (bus fault)
<b>Interfaces and Connectors</b>	Ethernet	2 * IEEE 802.3 100BASE-TX / 10BASE-T, managed Ethernet switch for daisy chain topology Connectors: RJ45 Protocol: EtherNet/IP RESTful API interface for device configuration
	PROFIBUS PA	Up to 4 PROFIBUS PA (MBP) segments (refer to the section "Order Numbers"), Bus-powered Medium Attachment Unit (MAU): Fieldbus voltage range: 9 VDC ... 32 VDC, current consumption 10 mA, Connectors: 3-position screw connection, galvanically isolated
<b>Physical Properties</b>	Dimensions (H x W x D)	100 mm x 35 mm x 115 mm
	Weight	Approx. 0.25 kg
	Power Supply	18 VDC ... 32 VDC; SELV/PELV power supply mandatory Typical input current: 200 mA, maximum input current: 1 A (allowing for in-rush current at switch-on) No power supply to PROFIBUS PA segments through pnGate PA
	Typical Power Loss	6 W
	Operating / Storage Temperature	-40 °C ... +60 °C / -40 °C ... +85 °C (see detailed mounting description in user manual)
	Relative Humidity	10 % ... 95 %, non-condensing
	Cooling	Convection, no fan
	Coating	Conformal coating based on ANSI / ISA-S71.04 G3
	Mounting	DIN rail 35 mm
	Protection Class	IP20

## Scope of Delivery

Hardware	epGate PA Gateway
Documentation	On Website

## Order Numbers

GCA-CL-024702	<b>epGate PA</b> , 2 channel, EtherNet/IP to PROFIBUS-PA Gateway. <b>Supports up to 2 PROFIBUS PA segments</b> (up to 32 PA devices).
GCA-CL-024704	<b>epGate PA</b> , 4 channel, EtherNet/IP to PROFIBUS-PA Gateway. <b>Supports up to 4 PROFIBUS PA segments</b> (up to 64 PA devices).

## Additional Products and Services

LRL-DY-134501	<b>dataFEED OPC Suite</b> , Version 4.01 and higher, including all supported PLC protocols, support for OPC UA, access for any number of dataFEED OPC Tunnel Clients, for simultaneous access to a total of up to 100 OPC UA Servers, OPC Servers and OPC Tunnel Servers, and many more Functionalities such as Database and File Access, Data Exchange, Optimizer, Concentrator and Bridge
GCA-CN-024708	<b>epGate PB</b> , EtherNet/IP to PROFIBUS Gateway. <b>Supports up to 2 PROFIBUS PA segments</b> (up to 32 PA devices, MBP physical layer) <b>and 1 PROFIBUS DP segment</b> (RS485).
GCA-CN-024706	<b>epGate DP</b> , EtherNet/IP to PROFIBUS DP-Gateway. Supports 1 PROFIBUS DP segment (RS485).

Your local Softing contact:

# SEITA

Soluciones en Instrumentación,  
Automatización y Control Industrial

[www.seita.com.co](http://www.seita.com.co)

<http://industrial.softing.com>

optimize!  
**softing**